EVOKES



The refrigerated merchandiser designed for performance and built to last







20% Greater CapacityWhen compared with competitors

Product Flexibility

Configurable to almost any package size

Healthy Safety

Programmable by selections, range and row





Optional





Outdoor Package

Impact resistance Lexan window cover, rain guards and anti-pry covers



Heated Glass Optional

Eliminate condensation and fogging



Standard Backlit Braille Keypad









100% Brighter **LED Lighting**

Payment System Versatility









Cold Food Configuration Shown

Evoke Combo 5 Outdoor					
Up to 60 Items					
Varies with tray configuration					
All Industry standard MDB Compatible Devices					
DEX/UCS					
Super 1/3 HP, R134a or R-513a Closed System					
Domestic: 115 VAC/60Hz, 8 AMPS International: 230 VAC/50Hz, 4 AMPS With Heated Glass Option: 115 VAC/60Hz, 9 AMPS International: 230 VAC/50Hz, 4.5 AMPS					
Height	72" (183 cm)	Width	45" (114.3 cm)	Depth	40" (101.6 cm)
*830 lbs. (376.5 kg) *Varies with tray configuration and options.					
Outdoor Package, FLEX Controller, LED Lighting, iVend® Sensor System, 9 Select Can & Bottle Trays, Door Switch, Delivery Assist Box					
6th Tray, Dual Helix, Motor Pairing, 10 Select Can/Bottle, Heated Glass, High Capacity Can Tray, <i>inDEX</i> Tool, Custom Graphics					
	Up to 60 Varies wi All Indust DEX/UCS Super 1/3 Domestic Internatic With Hea Internatic Height *830 lbs. Outdoor I 9 Select 6th Tray, Heated G	Up to 60 Items Varies with tray configu All Industry standard M DEX/UCS Super 1/3 HP, R134a or Domestic: 115 VAC/60- International: 230 VAC/6 With Heated Glass Optic International: 230 VAC/6 Height 72" (183 cm) *830 Ibs. (376.5 kg) */ Outdoor Package, FLEX 9 Select Can & Bottle Ti 6th Tray, Dual Helix, Mo Heated Glass, High Cap	Up to 60 Items Varies with tray configuration All Industry standard MDB Compa DEX/UCS Super 1/3 HP, R134a or R-513a C Domestic: 115 VAC/60Hz, 8 AMPS International: 230 VAC/50Hz, 4 AN With Heated Glass Option: 115 VA International: 230 VAC/50Hz, 4.5 // International: 230 VAC/50Hz, 4.5 // Width *830 Ibs. (376.5 kg) *Varies with Outdoor Package, FLEX Controller 9 Select Can & Bottle Trays, Door 6th Tray, Dual Helix, Motor Pairing Heated Glass, High Capacity Can	Up to 60 Items Varies with tray configuration All Industry standard MDB Compatible Devices DEX/UCS Super 1/3 HP, R134a or R-513a Closed System Domestic: 115 VAC/60Hz, 8 AMPS International: 230 VAC/50Hz, 4 AMPS With Heated Glass Option: 115 VAC/60Hz, 9 AMF International: 230 VAC/50Hz, 4.5 AMPS Height 72" Width 45" (114.3 cm) *830 lbs. (376.5 kg) *Varies with tray configura Outdoor Package, FLEX Controller, LED Lighting, 9 Select Can & Bottle Trays, Door Switch, Delive 6th Tray, Dual Helix, Motor Pairing, 10 Select Cal Heated Glass, High Capacity Can Tray, inDEX Too	Up to 60 Items Varies with tray configuration All Industry standard MDB Compatible Devices DEX/UCS Super 1/3 HP, R134a or R-513a Closed System Domestic: 115 VAC/60Hz, 8 AMPS International: 230 VAC/50Hz, 4 AMPS With Heated Glass Option: 115 VAC/60Hz, 9 AMPS International: 230 VAC/50Hz, 4.5 AMPS Height 72" Width 45" Depth (114.3 cm) Depth *830 lbs. (376.5 kg) *Varies with tray configuration and of the configurati

induced to unity you are even products possible, we committee a migratery performance and as soon specimental as a support of the change without notice. The manufacturer makes no warranties or representations of compliance with any local, state, antional or international requirements for the operation of the equipment in any application for which it is capable of being used beyond approvals listed on the product. Any purchaser is required to make an independent analysis of the fitness and legality of the product's usage before it is deployed and must continue to monitor the potential changing nature of compliance requirements. The manufacturer expressly disclaims responsibility for compliance with any laws and affirmatively requires any buyer to make an independent analysis of the fitness and legal basis of any use or application of the subject unit.





